

**41090021**

## 1st2nd auxiliary contact pre-break N position NO/NC SIRCOVER 125-1600A



### General characteristics

- Up to 2 NO/NC auxiliary contacts (1 fitted as standard).
- Connection to the control circuit by 6.35 mm fast-on terminal.
- Electrical characteristics : 30,000 operations.
- Low level AC: contact us.

### Link to the reference



<https://emea.socomec.com/en/reference/41090021>

Pre-breaking and signalling of positions I and II: 1 to 2 NO/NC auxiliary contacts in each position.

### Classification

|            |          |
|------------|----------|
| UNSPSC     | 39122205 |
| ETIM Class | EC000041 |
| IGCC       | 5177     |

### Commerce

|                       |            |
|-----------------------|------------|
| Effective date        | 1997-04-16 |
| Offer Life Cycle Code | 40         |
| Country of origin     | CN         |

### ETIM - Electrical characteristics

|                                                |    |
|------------------------------------------------|----|
| Number of contacts as normally open contact    | 2  |
| Number of contacts as normally closed contact  | 2  |
| Rated operation current Ie at AC-15, 230 V [A] | 12 |

### ETIM - Mechanical characteristics

|                             |                         |
|-----------------------------|-------------------------|
| Type of electric connection | Flat plug-in connection |
| Mounting method             | Front fastening         |

### ETIM - Technical features

|             |            |
|-------------|------------|
| Model       | Integrable |
| Lamp holder | None       |

### Logistics

|                                 |               |
|---------------------------------|---------------|
| GTIN/EAN                        | 3596031205554 |
| Customs number                  | 8536500700    |
| Price unit                      | PC            |
| Weight of the packing unit [kg] | 0.02          |
| Length of the packing unit [m]  | 0.015         |
| Width of the packing unit [m]   | 0.102         |
| Depth of the packing unit [m]   | 0.119         |

### Norms

|                         |     |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

### Technical Characteristics

|                             |                                                                      |
|-----------------------------|----------------------------------------------------------------------|
| Weight [kg]                 | 0.02                                                                 |
| Number change-over contacts | 1                                                                    |
| Number NC contacts          | 1                                                                    |
| Number NO contacts          | 1                                                                    |
| Type                        | Pre-break auxiliary contact 1st or 2nd NO/NC for SIRCOVER 125A-1600A |