


39940405

Auxiliary contacts for 2 pole 14x51 50A NO/NC for 2 pole

Fuse blown detection device for switch with NFC/DIN fuse with striker.



General characteristics

- For fuse cartridge with striker (size 14 x 51; 22 x 58; 0; 1; 2; 3 and 4).
- Electrical principle: an NO/NC auxiliary contact detects that the fuse has blown.
- Connection to control circuit: 6.35 mm fast-on terminal.
- Mechanical specifications: 30,000 operations.

Link to the reference



<https://emea.socomec.com/en/reference/39940405>

Classification

UNSPSC	39122233
ETIM Class	EC002498
IGCC	5291

Commerce

Effective date	1991-04-25
Offer Life Cycle Code	40
Country of origin	FR

Environmental impact

Carbon footprint - Lifecycle total [kg CO ₂ eq.]	126
---	-----

Logistics

GTIN/EAN	3596031195244
Customs number	8536500700
Price unit	PC
Weight of the packing unit [kg]	0.026
Length of the packing unit [m]	0.08
Width of the packing unit [m]	0.055
Depth of the packing unit [m]	0.02

Technical Characteristics

Weight [kg]	0.026
Fuse size	14x51
Number of poles	2
Number of auxiliary contacts	1NO+1NC
Size	1/11
Type	1st aux. contact