48250082

Energy Meter DIRIS A-20 Optional Modbus RS485 communication module



Additional modules that give the user flexibility throughout the service life of the product. Communication modules and additional digital or analogue inputs/outputs can be used to increase the range of functionality of the device.

Strong points

- Flexible
- Versatile

General characteristics

- Pulse outputs.
- MODBUS communication.
- PROFIBUS DP communication.
- Analogue outputs.
- 2 inputs / 2 outputs.
- Memory.
- Ethernet communication.
- Ethernet communication + RS485 MODBUS gateway.
- Temperature inputs

Link to the reference

https://emea.socomec.com/en/reference/48250082

Classification

UNSPSC	83101808
ETIM Class	EC002295
IGCC	6042

Commerce

Effective date	2004-07-15
Offer Life Cycle Code	40
Country of origin	HU

Environmental impact

Carbon footprint - Lifecycle total [kg CO_2 eq.]	5028
Carbon footprint - Manufacturing [A1-A3] [kg CO_2 eq.]	6
Use scenario	9 years / European mix

ETIM - Technical features

Type of accessory/spare part	Other

Logistics

GTIN/EAN	3596031755349
Customs number	8517620000
Price unit	PC
Weight of the packing unit [kg]	0.13
Length of the packing unit [m]	0.025
Width of the packing unit [m]	0.12
Depth of the packing unit [m]	0.08

Technical Characteristics

Type	Optional Modbus RS485 communication module