48290280

LoRaWan monitoring RJ9 cable DIRIS D-30 display - Length 1.5m

Socomec RJ9 cables connect DIRIS B or DIRIS Digiware I-4x to the remote DIRIS D-30 screen for the display of measurements.
As the RJ9 cable also carries the power supply to the DIRIS D-30 screen, no additional power supply is needed.

General characteristics

- Available in 1.5m and 3m.
- 600V insulated cables.
- Data communication and power supply to remote display.
- Used with DIRIS B or DIRIS Digiware I-4x.

Link to the reference

https://emea.socomec.com/en/reference/48290280

Classification

UNSPSC	83101808
ETIM Class	EC001262
IGCC	6042

Commerce

Effective date	2013-11-22
Offer Life Cycle Code	40
Country of origin	CN

ETIM - Mechanical characteristics

Length [m]	1.5
Colour outer sheath	Grey
Anti-kink sleeve	None
Colour anti-kink sleeve	Other
Cable construction	2x2
AWG-size	26
Cable type	U/UTP

ETIM - Technical features

Category	5
Type of connector connection 1	RJ9 4(2)
Type of connector connection 2	RJ9 4(2)
Locking lever	No
Fire retardant version	No
Oil resistant according to EN IEC 60811-404	Yes
Pin assignment	1:1
NVP value [%]	70

Logistics

GTIN/EAN	3596032776787
Customs number	8544429090
Price unit	PC
Weight of the packing unit [kg]	0.04
Length of the packing unit [m]	0.04
Width of the packing unit [m]	0.105
Depth of the packing unit [m]	0.02

Norms

Conformity to standards	IEC UL

Technical Characteristics

Height [mm]	1500
Connector	RJ9
Length	1.5 m
Type	Connects DIRIS D-30 display to DIRIS B PMD and DIRIS Digiware I-4x modules