50314010

Hexagonal insulator Height 40 M10 female to female



With SOCOMEC's insulating bar supports you can:
- mount and attach the busbars inside the electrical panel,
- cope with the forces experienced by the busbars during a short circuit

Strong points
- Insulating materials
- Durability
- Adaptability

General characteristics
- Polyester without halogen.
- UL94 VO self-extinguishing.
- Colour red RAL 3002.
- Operating temperature from -40 °C to +130 °C.
- Deformation under load temperature (ASTM D643): > 200 °C.
- Dielectric constant (ASTM D150): 4/5.
- Arc resistance (ASTM D495): > 180 s.
- Water absorption (ASTM D570):

Compliance with standards
- IEC 61439-1
- IEC 60865-1

Link to the reference

https://emea.socomec.com/en/reference/50314010

Classification

UNSPSC	39121321
ETIM Class	EC001166
IGCC	4462

Commerce

Effective date	2003-11-26
Offer Life Cycle Code	40
Country of origin	IN

ETIM - Electrical characteristics

Number of poles	1

Logistics

GTIN/EAN	3596031723959
Customs number	8546901000
Price unit	PC
Weight of the packing unit [kg]	0.085
Length of the packing unit [m]	0.04
Width of the packing unit [m]	0.04
Depth of the packing unit [m]	0.04

Norms

Conformity to standards	IEC

Technical Characteristics

Height [mm]	40
Width [mm]	40
Depth [mm]	40
Weight [kg]	0.085
Diameter	M10
Rated voltage	2000 VAC
Type	Hexagonal