

54003040

Terminal lug 45Nm 24mm 3P 400A



General characteristics

- Ratings: 160 to 630 A.
- Number of poles: 3 and 4.
- Material: tin-plated aluminium.

Compliance with standards

- IEC 60947-1 (if mounted to Socomec devices)
- NF C 63-060
- NF C 63-062

Link to the reference



<https://emea.socomec.com/en/reference/54003040>

SOCOMEc cage terminals are connection accessories that can be fixed onto the power terminals of SOCOMEc load break switches, changeover switches and fuse combination switches. They enable a direct terminal-free connection to rigid copper and aluminium conductors, with integration under the IP2 protective cover.

Classification

UNSPSC	39121421
ETIM Class	EC002498
IGCC	4586

Commerce

Effective date	1993-02-23
Offer Life Cycle Code	40
Country of origin	FR

ETIM - Technical features

Type of accessory/spare part	Connection terminal
Accessory	Yes
Spare part	No

Logistics

GTIN/EAN	3596031346844
Customs number	8536901000
Price unit	PC
Weight of the packing unit [kg]	0.55
Length of the packing unit [m]	0.033
Width of the packing unit [m]	0.055
Depth of the packing unit [m]	0.113

Norms

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Height [mm]	38
Width [mm]	32
Depth [mm]	71.5
Weight [kg]	0.55
Number of poles	3
Rated current [A]	315..400
Section	240