

**21134001**

## Auxiliary contact position NO+NC COMO 25-125A



There are two types of auxiliary contact, one for back plate mounting and one for door mounting. NO+NC auxiliary contacts per device (1 on each side of the device).

Link to the reference



<https://emea.socomec.com/en/reference/21134001>

### Classification

|            |          |
|------------|----------|
| UNSPSC     | 39122205 |
| ETIM Class | EC000041 |
| IGCC       | 5176     |

### Commerce

|                       |            |
|-----------------------|------------|
| Effective date        | 2017-01-16 |
| Offer Life Cycle Code | 40         |
| Country of origin     | DE         |

### ETIM - Mechanical characteristics

|                             |       |
|-----------------------------|-------|
| Type of electric connection | Other |
|-----------------------------|-------|

### ETIM - Technical features

|             |      |
|-------------|------|
| Lamp holder | None |
|-------------|------|

### Logistics

|                                 |               |
|---------------------------------|---------------|
| GTIN/EAN                        | 3596033000386 |
| Customs number                  | 8536500700    |
| Price unit                      | PC            |
| Weight of the packing unit [kg] | 0.02          |
| Length of the packing unit [m]  | 0.05          |
| Width of the packing unit [m]   | 0.034         |
| Depth of the packing unit [m]   | 0.022         |

### Norms

|                         |     |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

### Technical Characteristics

|                             |                                 |
|-----------------------------|---------------------------------|
| Weight [kg]                 | 0.02                            |
| Number change-over contacts | 2                               |
| Number NC contacts          | 1                               |
| Number NO contacts          | 1                               |
| Type                        | Auxiliary contact NO+NC 25-125A |