

21193312

External operation handle 0-1 type MC1 Black IP65

Accessories for operating the switch.



General characteristics

- The direct operation escutcheon plate adds 4 mm on each side of the 2 and 3-pole switch.
- The external control requires the operator to isolate the solar strings prior to any intervention on the installation.
- External controls are user-friendly and adapted to meet the requirements of residential installations, large roofs and ground-based generators.

Link to the reference



<https://apac.socomec.com/en/reference/21193312>

Classification

UNSPSC	31162801
ETIM Class	EC000229
IGCC	3038

Commerce

Effective date	2012-01-14
Offer Life Cycle Code	40
Country of origin	PL

Environmental impact

Carbon footprint - Lifecycle total [kg CO ₂ eq.]	1
Carbon footprint - Manufacturing [A1-A3] [kg CO ₂ eq.]	1
Use scenario	20 years / European mix

ETIM - Mechanical characteristics

Colour	Black
Degree of protection (NEMA)	Other

ETIM - Technical features

With key lock	No
Padlock locking	No
Suitable for emergency stop	No
With extension shaft	No
Suitable for power circuit breaker	No
Suitable for switch disconnecter	Yes

Logistics

GTIN/EAN	3596032792770
Customs number	8538909999
Price unit	PC
Weight of the packing unit [kg]	0.086
Length of the packing unit [m]	0.035
Width of the packing unit [m]	0.068
Depth of the packing unit [m]	0.125

Norms

Conformity to standards	UL
-------------------------	----

Technical Characteristics

Weight [kg]	0.1
Color	Black
Control operator	External operation handle 0-1
Degree of protection (IP)	IP65
Model	MC1