47290205

ISOM DIGIWARE D-75, Ethernet output with Webserver



The power monitoring interfaces ISOM Digiware D-55 and D-75 allow the following:
- A local visualisation of data from ISOM Digiware L-60 and F-60 modules, but also from the other modules connected to the Digiware network or from COUNTIS E and DIRIS A over
the RS485 bus.
- Power supply of Digiware modules.
- Access to this data over Ethernet.
Via an RS485 connection, the ISOM Digiware screen also acts as a gateway, centralising all measurements from the measuring devices and making this information available on Ethernet.
Version specially designed for healthcare establishments.

Strong points

- High-resolution graphic screen
- Secure power supply
- Ergonomic and easy to use
- Centralises measurement points
- Email notifications
- Embedded web server (D-75)

Compliance with standards

- IEC 61557-8
- IEC 61557-9
- IEC 61557-12
- ISO 14025

Link to the reference

https://emea.socomec.com/en/reference/47290205

Technical Characteristics

Height [mm]	96
Width [mm]	96
Depth [mm]	31
Communication ports	3
Communication protocols	Digiware, Modbus TCP, Modbus RTU
Model	D-75
Size	96x96 mm
Type	Ethernet, Webserver

ETIM - Technical features

Type of display	LCD
Visible diagonal screen size [inch]	3.5
Number of pixels, horizontal	350
Number of pixels, vertical	160
With on-screen keyboard	Yes
With touch screen	No
Mouse-cursor control integrated	No
With HW-interface PS2	No

ETIM - Electrical characteristics

Supply voltage DC [V]	24..24
Voltage type (supply voltage)	DC

ETIM - Mechanical characteristics

Colour display	No
Rail mounting possible	Yes
Wall mounting/direct mounting	Yes
Front built-in possible	Yes
Rack-assembly possible	No
Degree of protection (IP)	IP65
Width [mm]	96
Height [mm]	96
Depth [mm]	31
Operating temperature [°C]	10..55

Environmental impact

Carbon footprint - Lifecycle total [kg CO_2 eq.]	114
Carbon footprint - Manufacturing [A1-A3] [kg CO_2 eq.]	12

PEP Filename	SOCO-00043-V01.02-EN.pdf
Materials and substances	
EU REACH	Does not contain SVHC
EU RoHS	Compliant
Norms	
Conformity to standards	IEC
Commerce	
Description	Control and power supply interfaces ISOM DIGIWARE D-75 Ethernet output with Webserver Digiware, Modbus TCP/RTU communication protocols with 3 communication ports
Effective date	2018-10-01
Offer Life Cycle Code	40
Country of origin	FR
Logistics	
GTIN/EAN	3596033001864
Customs number	8528590090
Price unit	PC
Weight of the packing unit [kg]	0.29
Length of the packing unit [m]	0.11
Width of the packing unit [m]	0.09
Depth of the packing unit [m]	0.115
Classification	
UNSPSC	39122309
ETIM Class	EC004862
IGCC	5343