48290593

RJ12 connection cable 1m x6



The RJ12 connections allow you to connect modules very quickly and to automatically configure connected current sensors:
- communication address,
- load type,
- sensor type and ratio,
- automatic rating and verification of current travel direction.

Wiring errors are also prevented and installation is simplified.

General characteristics
- Plug & Play.
- Colour coded.
- Multiple lengths.

Compliance with standards
- IEC 61557-12
- UL 61010 Guide FTRZ/PICQ File E257746

Link to the reference

https://emea.socomec.com/en/reference/48290593

Classification

UNSPSC	83101808
ETIM Class	EC001262
IGCC	6042

Commerce

Effective date	2014-01-10
Offer Life Cycle Code	40
Country of origin	TH

ETIM - Mechanical characteristics

Length [m]	1
Colour outer sheath	Grey
Anti-kink sleeve	None
Cable construction	Other
AWG-size	26
Cable type	U/UTP

ETIM - Technical features

Category	5
Type of connector connection 1	RJ12 6(6)
Type of connector connection 2	RJ12 6(6)
Locking lever	No
Fire retardant version	No
Oil resistant according to EN IEC 60811-404	Yes
Pin assignment	1:1
NVP value [%]	70

Logistics

GTIN/EAN	3596032781965
Customs number	8544429090
Price unit	PC
Weight of the packing unit [kg]	0.16
Length of the packing unit [m]	0.04
Width of the packing unit [m]	0.12
Depth of the packing unit [m]	0.1

Norms

Conformity to standards	IEC UL

Technical Characteristics

Height [mm]	1000
Color	Red, Black, Yellow, Blue, Green, Purple
Connector	RJ12
Length	1 m

Type	Connection cable for TE, TR/iTR, TF current sensors