

67220400

DIN Fuselink gG Knife-edge fuse without striker 400A 500 VAC



SOCOMEc industrial fuses protect installations and people from overcurrents for any low voltage electrical circuit.

Strong points

- High-performance
- Increased reliability
- Improved safety

Compliance with standards

- IEC 60269-1
- DIN EN 60269-1
- NF EN 60269-1
- IEC 60269-2
- NF EN 60269-2

Link to the reference



<https://emea.socomec.com/en/reference/67220400>

Technical Characteristics

Height [mm]	61
Width [mm]	152.5
Depth [mm]	60
Weight [kg]	0.62
Fuse melting indicator	without striker
Fuse size	S2
Rated voltage	500 VAC
Rated current [A]	400
Type	gG

ETIM - Technical features

Fuse construction type according to IEC 60269	NH2
---	-----

ETIM - Electrical characteristics

Voltage type	AC
Rated current [A]	400
Rated voltage AC [V]	500

ETIM - Mechanical characteristics

Type of fuse status indicator	None
-------------------------------	------

Norms

Conformity to standards	IEC
-------------------------	-----

Commerce

Effective date	1988-04-15
Offer Life Cycle Code	40
Country of origin	HU

Logistics

GTIN/EAN	3596031391363
Customs number	8536109090
Price unit	PC
Weight of the packing unit [kg]	0.62
Length of the packing unit [m]	0.05
Width of the packing unit [m]	0.15
Depth of the packing unit [m]	0.075

Classification

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908