

68520160

DIN Fuselink gG Knife-edge fuse with striker 160A 500 VAC



SOCOMEc industrial fuses protect installations and people from overcurrents for any low voltage electrical circuit.

Technical Characteristics

Height [mm]	48
Width [mm]	127.5
Depth [mm]	45
Weight [kg]	0.29
Fuse melting indicator	with striker
Fuse size	S0
Rated voltage	500 VAC
Rated current [A]	160
Type	gG

ETIM - Technical features

Fuse construction type according to IEC 60269	NH0
---	-----

ETIM - Electrical characteristics

Voltage type	AC
Rated current [A]	160
Rated voltage AC [V]	500

Norms

Conformity to standards	IEC
-------------------------	-----

Commerce

Effective date	1988-04-15
Offer Life Cycle Code	40
Country of origin	ES

Logistics

GTIN/EAN	3596031408108
Customs number	8536109090
Price unit	PC
Weight of the packing unit [kg]	0.3
Length of the packing unit [m]	0.07
Width of the packing unit [m]	0.06
Depth of the packing unit [m]	0.13

Classification

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908

Strong points

- High-performance
- Increased reliability
- Improved safety

Compliance with standards

- IEC 60269-1
- DIN EN 60269-1
- NF EN 60269-1
- IEC 60269-2
- NF EN 60269-2

Link to the reference



<https://emea.socomec.com/en/reference/68520160>