68720400

DIN Fuselink gG Knife-edge fuse with striker 400A 500 VAC

SOCOMEC industrial fuses protect installations and people from overcurrents for any low voltage electrical circuit.

Strong points

- High-performance
- Increased reliability
- Improved safety

Compliance with standards

- IEC 60269-1
- DIN EN 60269-1
- NF EN 60269-1
- IEC 60269-2
- NF EN 60269-2

Link to the reference

https://emea.socomec.com/en/reference/68720400

Technical Characteristics

Height [mm]	61
Width [mm]	152.5
Depth [mm]	60
Weight [kg]	0.578
Fuse melting indicator	with striker
Fuse size	S2
Rated voltage	500 VAC
Rated current [A]	400
Type	gG

ETIM - Technical features

Fuse construction type according to IEC 60269	NH2

ETIM - Electrical characteristics

Voltage type	AC
Rated current [A]	400
Rated voltage AC [V]	500

Norms

Conformity to standards	IEC

Commerce

Effective date	1988-04-15
Offer Life Cycle Code	40
Country of origin	HU

Logistics

GTIN/EAN	3596031408542
Customs number	8536109090
Price unit	PC
Weight of the packing unit [kg]	0.578
Length of the packing unit [m]	0.07
Width of the packing unit [m]	0.055
Depth of the packing unit [m]	0.16

Classification

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908