


41AC3063

Manual Transfer Switch body SIRCOVER I-0-II 3P 630A



Strong points

- A complete range
- Easy to connect
- Stable positions
- On-load switching

General characteristics

- Range from 125A to 3200A.
- Available in 3P or 4P.
- Direct handle or external handle.

Compliance with standards

- IEC 60947-6-1
- IEC 60947-3
- GB/T 14048.11

Link to the reference



<https://emea.socomec.com/en/reference/41AC3063>

SIRCOVER products are manually operated transfer switches with positive break indication, for open-transition switching (I-0-II) available in 3 or 4 pole.

They provide on-load transfer between two sources for any low voltage power circuit, as well as safety isolation by double breaking per pole. Other applications include source inversion (e.g. to change the direction of a motor) or grounding/earthing.

Classification

UNSPSC	39122205
ETIM Class	EC000216
IGCC	5177

Commerce

Description	Manually Operated Transfer Switch SIRCOVER, switching type I-0-II, frame B5, 3P 630A, direct operation with handle type J2 or external operation with handle type S2. Delivered without handle
Effective date	2012-05-04
Offer Life Cycle Code	40
Country of origin	TN

Environmental impact

Carbon footprint - Lifecycle total [kg CO ₂ eq.]	385
Carbon footprint - Manufacturing [A1-A3] [kg CO ₂ eq.]	94
PEP Filename	SOCO-00074-V01.01-EN.pdf

ETIM - Electrical characteristics

Max. rated operation voltage Ue AC [V]	1000
Rated operating voltage [V]	400..690
Rated permanent current Iu [A]	630
Rated permanent current at AC-23,400 V [A]	630
Rated permanent current at AC-21,400 V [A]	630
Rated short-time withstand current Icw [kA]	12.6
Rated operation power at AC-23,400 V [kW]	280
Switching power at 400 V [kW]	280
Conditioned rated short-circuit current Iq [kA]	50
Number of poles	3

ETIM - Mechanical characteristics

Suitable for floor mounting	No
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	No
Suitable for intermediate mounting	Yes
Colour control element	Black
Degree of protection (IP), front side	IP20
Width [mm]	319

Height [mm]	260
Depth [mm]	295
ETIM - Technical features	
Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	No
Version as reversing switch	Yes
Number of switches	2
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Type of control element	Door coupling rotary drive
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection
Logistics	
GTIN/EAN	3596032675660
Customs number	8536508000
Price unit	PC
Weight of the packing unit [kg]	12
Length of the packing unit [m]	0.47
Width of the packing unit [m]	0.35
Depth of the packing unit [m]	0.305
Materials and substances	
EU REACH	Does not contain SVHC
EU RoHS	Compliant
Norms	
Conformity to standards	IEC
Technical Characteristics	
Height [mm]	260
Width [mm]	319
Depth [mm]	295
Weight [kg]	12
Control operator	Manual Direct : J2 / External : S2
Number of poles	3
Rated current [A]	630
Type	Manual I-0-II
Frame size	B5