

21190012

Direct operation handle 0-1 type MCO Black



Accessories for operating the switch.

General characteristics

- The direct operation escutcheon plate adds 4 mm on each side of the 2 and 3-pole switch.
- The external control requires the operator to isolate the solar strings prior to any intervention on the installation.
- External controls are user-friendly and adapted to meet the requirements of residential installations, large roofs and ground-based generators.

Link to the reference



<https://apac.socomec.com/en/reference/21190012>

Classification

UNSPSC	31162801
ETIM Class	EC000229
IGCC	3038

Commerce

Effective date	2012-01-14
Offer Life Cycle Code	40
Country of origin	PL

Environmental impact

Carbon footprint - Lifecycle total [kg CO ₂ eq.]	1
Carbon footprint - Manufacturing [A1-A3] [kg CO ₂ eq.]	1

ETIM - Mechanical characteristics

Colour	Black
--------	-------

ETIM - Technical features

With key lock	No
Padlock locking	No
Suitable for emergency stop	No
With extension shaft	No
Suitable for power circuit breaker	No
Suitable for switch disconnecter	Yes

Logistics

GTIN/EAN	3596032792756
Customs number	8538909999
Price unit	PC
Weight of the packing unit [kg]	0.03
Length of the packing unit [m]	0.055
Width of the packing unit [m]	0.03
Depth of the packing unit [m]	0.055

Norms

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Depth [mm]	24
Weight [kg]	0.03
Color	Black
Control operator	Direct operation handle 0-1
Model	MCO