

**60520016**

## gG curves with striker NFC Fuselink gG 16A 500 VAC



SOCOMEc industrial fuses protect installations and people from overcurrents for any low voltage electrical circuit.

### Strong points

- High-performance
- Increased reliability
- Improved safety

### Compliance with standards

- IEC 60269-1
- DIN EN 60269-1
- NF EN 60269-1
- IEC 60269-2
- NF EN 60269-2

### Link to the reference



<https://emea.socomec.com/en/reference/60520016>

### Classification

|            |          |
|------------|----------|
| UNSPSC     | 39121609 |
| ETIM Class | EC002704 |
| IGCC       | 4905     |

### Commerce

|                       |            |
|-----------------------|------------|
| Effective date        | 1988-04-15 |
| Offer Life Cycle Code | 40         |
| Country of origin     | ES         |

### ETIM - Electrical characteristics

|                                             |        |
|---------------------------------------------|--------|
| Rated current [A]                           | 16     |
| Rated voltage AC [V]                        | 500    |
| Voltage type                                | AC     |
| Utilization category according to IEC 60269 | gG     |
| Rated operating frequency [Hz]              | 50..60 |

### ETIM - Mechanical characteristics

|                               |                           |
|-------------------------------|---------------------------|
| Size                          | 14x51 mm                  |
| Type of fuse status indicator | Top fuse status indicator |

### ETIM - Technical features

|       |              |
|-------|--------------|
| Model | Ceramic fuse |
|-------|--------------|

### Logistics

|                                 |               |
|---------------------------------|---------------|
| GTIN/EAN                        | 3596031378272 |
| Customs number                  | 8536105090    |
| Price unit                      | PC            |
| Weight of the packing unit [kg] | 0.02          |
| Length of the packing unit [m]  | 0.0143        |
| Width of the packing unit [m]   | 0.0143        |
| Depth of the packing unit [m]   | 0.051         |

### Norms

|                         |     |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

### Technical Characteristics

|                        |              |
|------------------------|--------------|
| Height [mm]            | 51           |
| Width [mm]             | 14.3         |
| Depth [mm]             | 14.3         |
| Weight [kg]            | 0.02         |
| Fuse melting indicator | with striker |
| Fuse size              | 14x51        |
| Rated voltage          | 500 VAC      |
| Rated current [A]      | 16           |
| Type                   | gG           |