


60520020

gG curves with striker NFC Fuselink gG 20A 500 VAC



SOCOMEC industrial fuses protect installations and people from overcurrents for any low voltage electrical circuit.

Strong points

- High-performance
- Increased reliability
- Improved safety

Compliance with standards

- IEC 60269-1
- DIN EN 60269-1
- NF EN 60269-1
- IEC 60269-2
- NF EN 60269-2

Link to the reference



<https://emea.socomec.com/en/reference/60520020>

Classification

UNSPSC	39121609
ETIM Class	EC002704
IGCC	4905

Commerce

Effective date	1988-04-15
Offer Life Cycle Code	40
Country of origin	ES

ETIM - Electrical characteristics

Rated current [A]	20
Rated voltage AC [V]	500
Voltage type	AC
Utilization category according to IEC 60269	gG
Rated operating frequency [Hz]	50..60

ETIM - Mechanical characteristics

Size	14x51 mm
Type of fuse status indicator	Top fuse status indicator

ETIM - Technical features

Model	Ceramic fuse
-------	--------------

Logistics

GTIN/EAN	3596031378289
Customs number	8536105090
Price unit	PC
Weight of the packing unit [kg]	0.02
Length of the packing unit [m]	0.0143
Width of the packing unit [m]	0.0143
Depth of the packing unit [m]	0.051

Norms

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Height [mm]	51
Width [mm]	14.3
Depth [mm]	14.3
Weight [kg]	0.02
Fuse melting indicator	with striker
Fuse size	14x51
Rated voltage	500 VAC
Rated current [A]	20
Type	gG