

68730200

DIN Fuselink aM Knife-edge fuse with striker 200A 690 VAC



SOCOMEC industrial fuses protect installations and people from overcurrents for any low voltage electrical circuit.

Strong points

- High-performance
- Increased reliability
- Improved safety

Compliance with standards

- IEC 60269-1
- DIN EN 60269-1
- NF EN 60269-1
- IEC 60269-2
- NF EN 60269-2

Link to the reference



<https://emea.socomec.com/en/reference/68730200>

Technical Characteristics

Height [mm]	61
Width [mm]	152.5
Depth [mm]	60
Weight [kg]	0.578
Fuse melting indicator	with striker
Fuse size	S2
Rated voltage	690 VAC
Rated current [A]	200
Type	aM

ETIM - Technical features

Fuse construction type according to IEC 60269	NH2
---	-----

ETIM - Electrical characteristics

Voltage type	AC
Rated current [A]	200
Rated voltage AC [V]	690
Utilization category	aM

Norms

Conformity to standards	IEC
-------------------------	-----

Commerce

Effective date	1988-04-15
Offer Life Cycle Code	40
Country of origin	HU

Logistics

GTIN/EAN	3596031408597
Customs number	8536109090
Price unit	PC
Weight of the packing unit [kg]	0.578
Length of the packing unit [m]	0.145
Width of the packing unit [m]	0.065
Depth of the packing unit [m]	0.05

Classification

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908