48290186

Branch-circuit monitoring RJ45 cable Digiware bus - Length 5 m



The RJ45 connections allow you to connect modules very quickly and to automatically configure connected current sensors:
- communication address,
- load type,
- sensor type and ratio,
- automatic rating and verification of current travel direction.

Wiring errors are also prevented and installation is simplified.

General characteristics

- Available in different lengths.
- 600V insulated, can be in contact with busbars.
- Plug & Play.

Compliance with standards

- IEC 61557-12
- UL 61010 Guide FTRZ/PICQ File E257746

Link to the reference

https://emea.socomec.com/en/reference/48290186

Classification

UNSPSC	83101808
ETIM Class	EC001262
IGCC	6042

Commerce

Effective date	2014-06-04
Offer Life Cycle Code	40
Country of origin	TH

ETIM - Mechanical characteristics

Length [m]	5
Colour outer sheath	Yellow
Anti-kink sleeve	None
Colour anti-kink sleeve	Other
Cable construction	2x4
AWG-size	24
Cable type	U/UTP

ETIM - Technical features

Category	5
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Locking lever	No
Fire retardant version	No
Oil resistant according to EN IEC 60811-404	Yes
Pin assignment	1:1
NVP value [%]	70

Logistics

GTIN/EAN	3596032809881
Customs number	8544429090
Price unit	PC
Weight of the packing unit [kg]	0.2
Length of the packing unit [m]	0.15
Width of the packing unit [m]	0.13
Depth of the packing unit [m]	0.025

Norms

Conformity to standards	IEC UL

Technical Characteristics

Height [mm]	5000
Color	Yellow
Connector	RJ45

Length	5 m
Type	Digiware bus