

**57035001**

## Modular fuse holder for cylindrical fuses RM FUSE SWITCH 100A 1P



### Strong points

- Improved safety
- High breaking capacity
- Format and specific accessories

### Compliance with standards

- IEC 60269-2-1
- IEC 60269-1
- IEC 60269-2
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620
- CSA 265615
- UL E307648

### Link to the reference



<https://emea.socomec.com/en/reference/57035001>

RM are modular fuse disconnect switches for cylindrical fuses. They provide safety disconnection and protection against overloads and short-circuits in any low voltage electrical circuit.

RM: Non-signalling fuse disconnect switches for fuses without strikers.

### Classification

|            |          |
|------------|----------|
| UNSPSC     | 39121624 |
| ETIM Class | EC002705 |
| IGCC       | 4974     |

### Commerce

|                       |            |
|-----------------------|------------|
| Effective date        | 2012-06-25 |
| Offer Life Cycle Code | 40         |
| Country of origin     | ES         |

### ETIM - Electrical characteristics

|                                          |     |
|------------------------------------------|-----|
| Nominal voltage [V]                      | 690 |
| Number of poles                          | 1   |
| Concurrently switching neutral conductor | No  |

### ETIM - Mechanical characteristics

|                                     |          |
|-------------------------------------|----------|
| Mounting method                     | DIN rail |
| For fuse size                       | 22x58 mm |
| Width in number of modular spacings | 1        |
| Built-in depth [mm]                 | 49.5     |
| Degree of protection (IP)           | IP2X     |

### ETIM - Technical features

|                                |     |
|--------------------------------|-----|
| Lockable                       | Yes |
| With optical defect indication | No  |

### Logistics

|                                 |               |
|---------------------------------|---------------|
| GTIN/EAN                        | 3596032687069 |
| Customs number                  | 8536109090    |
| Price unit                      | PC            |
| Weight of the packing unit [kg] | 0.15          |
| Length of the packing unit [m]  | 0.085         |
| Width of the packing unit [m]   | 0.135         |
| Depth of the packing unit [m]   | 0.235         |

### Norms

|                         |           |
|-------------------------|-----------|
| Conformity to standards | IEC<br>UL |
|-------------------------|-----------|

### Technical Characteristics

|                        |            |
|------------------------|------------|
| Height [mm]            | 126.5      |
| Width [mm]             | 143        |
| Depth [mm]             | 76.5       |
| Weight [kg]            | 0.15       |
| Fuse melting indicator | no         |
| Fuse size              | 22x58      |
| Number of poles        | 1          |
| Rated current [A]      | 100        |
| Size                   | RM/RMS 100 |